

The Gund Company, Inc.
Saint Louis, Missouri U.S.A.

Tel: (314) 423-5200
Fax: (314) 423-9009

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT INFORMATION

PRODUCT NAME AND SYNONYMS:

Paper - Phenolic Composite (Sheets, Molded Shapes, Tubes or Laminated Products)

CAS NO. AND NAME: This material is a manufactured, non-hazardous product.

CHEMICAL FORMULA: Polymer

NAME AND ADDRESS:

THE GUND COMPANY, INC.
2121 WALTON ROAD
SAINT LOUIS, MISSOURI 63114
TEL 314 423 5200
FAX 314 423 9009

EMERGENCY TELEPHONE: Chemtrec (800) 424-9300

SECTION II - HAZARDOUS COMPONENTS

COMPONENT (CAS Registry No.)	WT. %	ACGIH TLV	OSHA PEL

Nuisance Dust		10mg/m ³ Total Dust	15mg/m ³ Total Dust

*** No ingredients with exposure limits are present in concentrations >1% in the product formulation. Nuisance dust may be generated if large quantities of composite are cut or machined.

SECTION III - PHYSICAL PROPERTIES

APPEARANCE AND ODOR: Solid, paper-based material. No discernible odor.

MOLECULAR WEIGHT: Not Applicable

SPECIFIC GRAVITY: Solid

SOLUBILITY IN WATER: None

pH: Not Applicable

The Gund Company, Inc.
Saint Louis, Missouri U.S.A.

Tel: (314) 423-5200
Fax: (314) 423-9009

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (DEGREES F< PENSKEY MARTINS CLOSED CUP): None

FIRE EXTINGUISHING MEDIA: Foam, Dry Chemical, Carbon Dioxide, Water spray as suitable for surrounding materials

FLAMMABLE LIMITS: LOWER: None UPPER: None

SPECIAL FIRE FIGHTING PROCEDURES: Use protective gear with self-contained breathing apparatus

UNUSUAL FIRE AND EXPLOSION HAZARDS: High dust concentrations from dry fabrication may be explosive if mixed with air and in the presence of an ignition source.

HAZARDOUS COMBUSTION PRODUCTS: CO₂, CO, HCN, similar to wood products.

SECTION V - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Stable at normal storage conditions. Avoid heating above 450°F.

INCOMPATIBILITY: Oxidizers, strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: CO₂, CO, HCN, similar to wood products.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD INFORMATION

EXPOSURE FROM ROUTINE USE: Dust can cause irritation to the eyes, nose, throat, lungs, and skin.

EFFECTS OF OVEREXPOSURE: Prolonged exposure to dust may cause irritation in eyes, nose, throat and/or mouth.

PROBABLE ROUTES OF EXPOSURE: Skin, eyes, inhalation

EMERGENCY FIRST AID PROCEDURES:

EYE CONTACT: For dust, rinse immediately with water. Remove contact lenses, then flush with large quantities of water for at least 15 minutes. Seek medical attention.

The Gund Company, Inc.
Saint Louis, Missouri U.S.A.

Tel: (314) 423-5200
Fax: (314) 423-9009

SKIN CONTACT: Routine skin contact with composite or composite dust is unlikely to cause any hazard.

INHALATION: For dust, remove to fresh air. Seek medical attention if necessary.

INGESTION: Ingestion of composite or composite dust is unlikely to occur in industrial or commercial use.

OTHER:

The resin used to make this plastic contains small amounts of formaldehyde. The cured plastic may evolve small amounts of formaldehyde when fabrication or heating of the product occurs. Air testing of representative fabrication operations indicates that formaldehyde releases are minimal and formaldehyde air concentrations are below regulatory standards. Formaldehyde has been identified as a skin sensitizer in low concentrations and as a probable human carcinogen (IARC-2A, pharyngeal cancer excess in formaldehyde exposed workers).

SECTION VII - TOXICITY DATA

ORAL: No tests have been performed.

DERMAL: No tests have been performed.

INHALATION: No tests have been performed.

EYE: No tests have been performed.

CARCINOGENICITY: Paper - Phenolic composite has not been evaluated for carcinogenicity.

SECTION VIII - SPECIAL PROTECTION INFORMATION

WORK and HYGIENE PRACTICES: Avoid getting dust in your eyes. Avoid blowing dust with compressed air. Avoid prolonged or repeated breathing of dust. Avoid open flame and contact with oxidizing agents. Use proper personal protection (see below).

STORAGE and HANDLING PRACTICES: No special handling requirements. Where dust is stored for disposal, keep in a cool area away from heat, ignition sources, and oxidizing agents.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:
Keep open ignition sources out of areas where dust is generated.

VENTILATION and ENGINEERING CONTROLS: Provide adequate general and local exhaust ventilation to maintain airborne concentrations below the exposure limits and to maintain healthful working conditions. To avoid static sparks, electrically ground and bond all equipment used in and around processes that involve dust generation. Enclose processes, where possible, to prevent/minimize dust dispersion into work areas.

The Gund Company, Inc.
Saint Louis, Missouri U.S.A.

Tel: (314) 423-5200
Fax: (314) 423-9009

RESPIRATORY PROTECTION: Where significant exposures to nuisance dust are possible, respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit-testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage must be implemented. If concentrations are below the TLV and/or PEL, a NIOSH approved disposable dust/mist respirator may be used for personal comfort. For concentrations above the TLV and/or PEL, but less than 10 times these limits, a NIOSH approved half-facepiece respirator equipped with dust/mist cartridges may be used. For concentrations greater than 10 times the TLV and/or PEL, consult the NIOSH respirator decision logic found in Publication No. 87-1-16 or ANSI Z88.2-1992. Note: ANSI Z88.2-1992 requires the use of a HEPA filter if the particle size distribution of the contaminant is unknown. *Warning! Air-purifying respirators do not protect workers in oxygen deficient atmospheres.*

EYE PROTECTION: Wear safety glasses or goggles if flying dust may blow into the eyes. Ensure compliance with OSHA's personal protective equipment standard (29 CFR 1910.133) for eye and face protection.

HAND and BODY PROTECTION: None Needed.

SECTION IX - SPILL, LEAK, AND DISPOSAL PROCEDURES

IN CASE MATERIAL IS SPILLED OR RELEASED: None - Solid Non-hazardous Material

SECTION X - REGULATORY INFORMATION

FDA: N/A

USDA: N/A

CPSC: N/A

TSCA: N/A

DOT: N/A

EPA: N/A

Additional Requirements for State of California: Warning: Laminate products contain formaldehyde, a substance known to the State of California to cause cancer. Laminates contain small amounts of residual formaldehyde that may be released in measurable quantities when stored in bulk quantities

The Gund Company, Inc.
Saint Louis, Missouri U.S.A.
EFFECTIVE DATE: June 21, 2000

Tel: (314) 423-5200
Fax: (314) 423-9009

SUPERSEDES: June 12, 1997

IMPORTANT: The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation, and verification. INTERNATIONAL PAPER MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. International Paper will not be responsible for claims relating to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading.